



## Compact zone valve QCV.

The space-saving QCV (Quick Compact Valve) from the Belimo ZoneTight™ product range is available as a 2-way characterised control valve with nominal diameters of DN 15 and DN 20 and also as a 3-way change-over ball valve with DN 15 and DN 20 nominal diameters. These valves provide numerous benefits:

- Tight-sealing characterised control valve prevents circulation losses
- Manually adjustable  $k_v$  values with the 2-way characterised control valves
- Automatic adaptation to set  $k_v$  value
- Minimum power consumption in operating and standby modes
- Compatible with 24 V, 230 V, open-close/3-point, modulating control and MP-Bus®

BELIMO  
**ZoneTight™**

In limited-space installation situations, the zero-leaking valves from the Belimo ZoneTight™ product family are the ideal solution for energy-saving smooth room and zone control.

**BELIMO®**

# Compact zone valve QCV.


## Robust, flexible, tight-sealing.



Chilled beams



Fan coil



Available with white housing cover



Simple manual  $k_v$  setting

### Versatile fields of application

- Fan coil
- Zone air heaters/air coolers
- Cooling ceilings and beams
- Floor heaters
- Radiators
- Heat pumps
- Boiler

### Convincing properties

- Compact overall structure
- Actuator installed without any tools
- Doesn't «stick» thanks to reliable ball valve technology
- Resistant to contamination
- Proven valve/actuator technology from Belimo

### 2-way characterised control valve with manually adjustable $k_v$ value



Type	Sort	Nominal diameter DN	$k_{VS}$ [m³/h]	Adjustable flow rates $k_v$ [m³/h]
C215Q-F	2-way	15	1.2	0.09 ... 1.2
C215Q-J	2-way	15	4.8	0.4 ... 4.8
C220Q-K	2-way	20	8	0.5 ... 8

### Power-saving actuators

- Compact rotary actuators
- Low power consumption
- Running time: 75 s/90°
- Degree of protection: IP40
- Open-close/3-point (AC/DC 24 V or 230 V)
- Modulating (AC/DC 24 V)
- «MP-Bus® light» (communicative, AC/DC 24 V) from Belimo
- Available with cable or terminals
- Electrical emergency control function

### 3-way change-over ball valve for safe switching between two circuits



Type	Sort	Nominal diameter DN	$k_{VS}$ [m³/h]
C315Q-H	3-way	15	2.5
C320Q-J	3-way	20	4

Belimo worldwide: [www.belimo.com](http://www.belimo.com)



5-year warranty



On site around the globe



Complete product range



Tested quality



Short delivery times



Comprehensive support

**BELIMO Automation AG**, Brunnenbachstrasse 1, CH-8340 Hinwil, Switzerland  
Tel. +41 43 843 61 11, Fax +41 43 843 62 68, [info@belimo.ch](mailto:info@belimo.ch)

**BELIMO**<sup>®</sup>